

Avery Dennison® Omni-View™

Prismatic Grade Reflective Sheeting
 Permanent Traffic Signage
 Pressure Sensitive Adhesive for Aluminum

Data Bulletin # PDB T-9500

Issued: May 1, 05

Updated: May 5, 06

Description:

Avery Dennison® Omni-View Prismatic Grade Reflective Sheeting is a super-high performance, durable, micro-prismatic retroreflective material. Omni-View can be specified for all traffic applications because of its bright performance at short, medium and long distances.

Omni-View is suitable for urban applications such as stop, yield, and street name signs where added sign brightness is needed to compete against background illumination. Omni-View is also suitable in high speed applications such as speed limit, warning and guide signs where long distance brightness ensures sign conspicuity and legibility.

Construction:

Face Film:	High gloss
Adhesive	Permanent Pressure Sensitive (Class 1).
Liner:	Poly Liner

Photometric Performance:

Minimum Coefficient of Retroreflection (R_A) (cd / lx / m²)

Observation Angle	Entrance Angle	White	Yellow	Green	Red	Blue	Fluorescent Yellow	Fluorescent Yellow-Green
0.2°	-4°	525	395	52	95	30	315	420
	30°	215	162	22	43	10	130	170
0.5°	-4°	310	230	31	56	18	185	245
	30°	135	100	14	27	6	81	110
1.0°	-4°	80	60	8.0	16	3.6	48	64
	30°	45	34	4.5	9	2.0	27	36

Colors & Specification Limits (Daytime)^A:

Color	1		2		3		4		Luminance (Y%)	
	x	y	X	y	x	y	x	Y	Min	Max
White	0.303	0.300	0.368	0.366	0.340	0.393	0.274	0.329	40	--
Yellow	0.498	0.412	0.557	0.442	0.479	0.520	0.438	0.472	24	45
Blue ^B	0.140	0.035	0.244	0.210	0.190	0.255	0.065	0.216	1.0	10
Green ^B	0.026	0.399	0.166	0.364	0.286	0.446	0.207	0.771	3.0	12
Red	0.648	0.351	0.735	0.265	0.629	0.281	0.565	0.346	3.0	15
Fluorescent Yellow	0.479	0.520	0.446	0.483	0.512	0.421	0.557	0.442	45	--
Fluorescent Yellow-Green	0.387	0.610	0.369	0.546	0.428	0.496	0.460	0.540	60	--

^AThe four pairs of chromaticity coordinates determine the acceptable color in terms of the CIE 1931 Standard Colorimetric System measured with Standard Illuminant D65.

^BThe saturation limit of green and blue may extend to the border of the CIE chromaticity locus for spectral colors

Avery Dennison® Omni-View continued...

Specifications:

Omni-View Series sheetings meets the requirements of ASTM D 4956 for Type XI sheeting as proposed by Avery Dennison. Consult your Avery Dennison Representative for information concerning additional world-wide specifications.

Physical Properties:

Outdoor Durability	Avery Dennison Omni-View, in standard colors, is a 12 year durable product when properly processed and applied. T-9513 Omni-View Fluorescent Yellow-Green and T-9511 Fluorescent Yellow is a 10 year durable product when properly processed and applied. Refer to the appropriate Avery Dennison product warranty for specific details and limitations.
Minimum Surface & Ambient Air Application Temperature	65°F (18°C) when applied with a squeeze roll applicator.
Application Surface	Flat surfaces only. Always pretest your specific substrate prior to application. Note: Wet method of application is not recommended for Avery Dennison Omni-View reflective sheeting.
Service Temperature Range	-40°F to 180°F (-40°C to 82°C)
Typical Film Caliper (w/adhesive)	17 to 18 mils
Shelf Life	One year when stored at the following temperature and conditions 68° - 77°F (20° - 25°C) and 50% ± 5%± R.H.
Other Tests:	Omni-View meets all other requirements set forth in ASTM D 4956 including Shrinkage, Flexibility, Liner removal, Adhesion, Impact resistance, Specular gloss and Outdoor weathering.

Application & Converting Information:

Omni-View is available 50 yard rolls of 24, 36 and 48 inch width.

The following Avery Dennison literature will provide complete information to the user for proper application, storage, and other requirements and is available from your Avery Dennison representative, from the Avery Dennison web-site www.reflectives.averydennison.com, or on request:

Approved screen printing inks and overlays:

Supplier	Series	System	Instructional Bulletins
Avery Dennison	4930 Inks	1 Part Solvent	#8.40
Avery Dennison	OL-2000	Acrylic Overlay	

Sign Mounting /Orientation:

Omni-View is omni-directional. It does not require a special orientation for mounting, and therefore, does not require an orientation arrow datum mark.

Avery Dennison® Omni-View continued...

Instructional Bulletins:	
Sheeting Care & Handling	#8.00
Substrate Requirements	#8.01
Application Techniques for PS Sheeting	#8.10
Steel Rule Die-Cutting	#8.20
Thermal Die Cutting	#8.20
Sign Cutting	#8.25
Screen Preparation	#8.30
Troubleshooting Printing & Processing	#8.34
Proper Sign Storage Booklet	#8.50

Color Availability:	
T-9500	White
T-9501	Yellow
T-9505	Blue
T-9507	Green
T-9508	Red
T-9511	Fluorescent Yellow
T-9513	Fluorescent Yellow-Green

Warranty:

WARRANTY: All statements, technical information and recommendations about Avery Dennison products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that Purchaser has independently determined the suitability of such products for its purposes. Avery Dennison products are warranted to be free from defects in material and workmanship for either one year (or the period stated on the specific product information literature in effect at time of delivery, if longer) from date of shipment if said product is properly stored and applied. It is expressly agreed and understood that Avery Dennison's sole obligation and Purchaser's exclusive remedy under this warranty, under any other warranty, express or implied, or otherwise, shall be limited to repair or replacement of defective product without charge at Avery Dennison's plant or at the location of product (at Avery Dennison's election), or in the event replacement or repairs is not commercially practical, to Avery Dennison's issuing Purchaser a credit reasonable in light of the defect in the product.

Avery Dennison's liability for defective products shall not exceed the purchase price paid therefore by Purchaser and in no event shall Avery Dennison be responsible for any incidental or consequential damages whether foreseeable or not, caused by defects in such product, whether such damage occurs or is discovered before or after replacement or credit, and whether or not such damage is caused by Avery Dennison's negligence.

NO EXPRESS WARRANTIES AND NO IMPLIED WARRANTIES, WHETHER OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR USE, OR OTHERWISE (EXCEPT AS TO TITLE), OTHER THAN THOSE EXPRESSLY SET FORTH ABOVE WHICH ARE MADE EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES, SHALL APPLY TO PRODUCTS SOLD BY AVERY DENNISON. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND MANUALLY SIGNED BY AN OFFICER OF AVERY DENNISON.

Avery Dennison , 6565 W. Howard, Niles, IL 60714, USA, 1-800-327-5917, www.reflectives.averydennison.com