

Basic equipment:

Engine

Water-cooled, 4-cylinder Kubota Turbo Diesel engine 3300 cm³. 62kW (83 HP) @ 2600 RPM.

Compressor

Screw compressor, capacity each 1800 L/min. at 10 bar. Air safety valve with silencer.

Chassis

Stable double profile frame construction. Engine, compressor and hydraulic pump in one unit mounted on vibration dampers.

Power steering

Fully hydraulically powered steering for directional stability. Turning circle 9.80 m.

Guide rod

Stabilised against vibrations and adjustable in all directions. Easy handling, telescopic system. Fixed to frame or turning with wheels.

Transmission

Hydrostatic, infinitely variable transmission 0-25 Km/h.

Hydraulic pump

Hydrostatic pump, 40 cm³.

Wheel motors

High-torque hydraulic piston motors with integrated full-torque electrohydraulic disc brakes.

Hydraulic oil tank

90 Litres.

Diesel oil tank

110 Litres.

Pressurized bead tanks

Bead capacity 200 L. 2 x 100 L. pressure tanks, centrally connected.

Operator section

Drivers section with 2 seats. The control panel, pneumatic section, electronics, steering wheel and instruments are connected to the drivers seat. The complete section can be slid from side to side within seconds and without the use of tools.

Electrical system

12 V/85 Amp alternator. Warning lights, rear lights, front lights, battery and relays.

Electronic control system

BM UNI-LINE-EUR 1

For up to 3 paint guns and 3 bead guns. The waterproof control panel is equipped with raised buttons and each button has its own symbol for easy operation. 10 markings can be pre-programmed. Automatic, semi-automatic and manual operation. Automatic remarking

correction of cycle start and stop. Display for line length, gap, speed, working hours and total marking distance. Optional remote start/stop function.

Motor bonnet

Easy access for service in left and right side.

Paint

Standard: RAL 1007. Other colours available on request.

Spray-plastic equipment:

Spray-plastic pressure tank

Pressurised 300 L tank oil-jacketed and indirectly heated by heat transfer oil. Vertical mixer with top foundation and bearings. Thermostatically controlled oil and material temperature.

Agitator transmission

Hydraulic transmission with motor, shaft, safety valve and on/off valve. Reversible mixer.

Burner system

Diesel oil burner or alternatively Propane burner

Heat transfer oil pump

Hydraulically driven.

Retainer

Basic frame and marker unit for 3 spray guns and 3 bead guns. Indirect heated, oil-jacketed and isolated.

Retainer lifting system

Adjustment of retainer height from driver's seat. Pneumatic cylinder, cylinder foundation and pneumatic solenoid valve.

Panel for pneumatic control

Control panel with pressure regulators and pressure gauges.

Spray-plastic gun

Automatic high-capacity sprayplastic gun. Consists of an oiljacketed gun body and a pneumatic cylinder. See also catalogue for our different types of gun.

Options:

Power steering

Fully hydraulically powered steering for directional stability. Turning circle 9.80 m.

Electronic skip-line controlBM UNI-LINE-EUR 1

For up to 3 paint guns and 3 bead guns. The waterproof control panel is equipped with raised buttons and each button has its own symbol for easy operation. 10 markings can be pre-programmed. Automatic, semi-automatic and manual operation. Automatic remarking correction of cycle start and stop. Display for line length, gap, road speed, working hours and total marking distance. Optional remote start/stop function.

Bead gun system

Please see brochure on guns

Gauges

For oil pressure.
For water temperature.
For diesel oil.

Hydraulic lifting of pointer

Lifting and lowering of pointer is controlled from the driver's seat.

Premark system

Electronically controlled premark system with telescopic foundation and ground distance wheel.

Driver's cabin

Foundation for reduction of vibrations, windscreen wiper, 50 mm noise silencing material in walls. Doors left and right. Operator controls and seat can be slid from left to right inside the cabin.

Driver's cabin heating and ventilation

Driver's cabin air condition

Dimensions + weight

Incl. equipment.
L: 4960 mm.
W: 1200 mm + equipment.
H: 2250 mm
incl. rotating light.
Weight: From 2600 up to 3800 kg.

Modification rights reserved.

