

# ITERLENE IN/400-S 1

## ANTISTRIPPING AGENT FOR HOT MIXES

### APPLICATION

ITERLENE IN/400-S 1 is a liquid anti-stripping agent, which is very active and of new generation, it guarantees a stable adhesion between bitumen and aggregate in every work condition (cold, humidity, acid aggregate).

ITERLENE IN/400-S 1 is very stable at the high stocking temperatures (170° C) in the bitumen, moreover it is very stable at the long warming times, without alteration of its activity.

ITERLENE IN/400-S 1 is particularly studied to be employed in hot and humid climate, with acid aggregates as (quartzite/porphyries).

### DOSAGE

The dosage of ITERLENE IN/400-S 1 varies from 0,2% to 0,4% of the bitumen weight according to the work conditions.

### COMPOSITION

Alkylamido-imidazo-poliamine.

### PHYSICAL PROPERTIES

Aspect	liquid
Density at 20° C	0,930 - 0,960
gr/cm <sup>3</sup>	
Flash Point	Over 200° C
Alkalinity	330 - 380
mg/gHCl	

### STOCKAGE

Possibly very tightly in closed drums and in places sheltered from the weather conditions.

### PACKAGE

In steel drums ( Kg. 200 net )

### SAFETY PRECAUTIONS

ITERLENE IN/400-S 1 is not dangerous either for use or for transport.